



GP

GENERAL PETROLEUM

www.generalpetroleum.de

Product Data Sheet (PDS)



**SYNCROGEN MTF
EP 140 API GL-5**

Published by:

Technical Department of
General Petroleum GmbH
Frankfurt, Germany

Last Update Date:

2/10/2025

SYNCROGEN MTF EP 140 API GL-5



SYNCROGEN MTF 140 GL 5 are universal transmission gear oils which can be applied in both manual gearboxes as well as in final drives, where API GL-5 quality oil is prescribed. These products can be used for the complete drive line. It contains special additives reducing fuel consumption and eliminating shifting problems. Due to this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures the oil is protected against thermal oxidation.

PERFORMANCE STANDARDS:

- API GL-5
- MIL-L-2105-D
- Mack GO-G
- ZF TE-ML 05A,12A
- MAN 342 N / MAN 342 type M-1

FEATURES & BENEFITS:

- Superior Extreme Pressure Performance: These Oils shows excellent EP (Extreme Pressure) characteristics providing an adequate protection even under high shock loads and vibrations.
- Excellent Resistance for Wear, Corrosion, Foaming and Oxidation: These Oils shows an excellent resistance against wear, corrosion and foaming as well as oxidation and ageing at elevated temperatures.

APPLICATIONS:

Recommended for use in manual gearboxes (synchronized or non-synchronized) as well as in final drives, where an API GL-5 quality oil is prescribed.

SYNCROGEN MTF

EP 140 API GL-5



TECHNICAL DATA

Sr.No	Properties	Test Methods	Results
01	Appearance	VISUAL	Clear
02	Color	ASTM D-1500	L4.0
03	R.D. at 85 ° F	ASTM D-1298/ D-7042	0.8962
04	R.D. at 15 ° C	ASTM D-1298/ D-7042	0.9056
05	Kinematic Viscosity@100C,cSt	ASTM D-445/ D-7042	29.95
06	Kinematic Viscosity@40C,cSt	ASTM D-445/ D-7042	433.25
07	Viscosity Index	ASTM D-2270/D-7042	98
08	Pour Point, ° C	ASTM D-97	-18
09	Water	By CRACKLE	-ve
10	P Content, %	ASTM D-6595	0.045

Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.